



ESP® helps prevent skidding and overturning, keeping you stable around turns.



ESP® reduces skidding for better grip on wet surfaces, gravel, snow or loose soil.



SUPER GRIP ON WET ROADS

When the truck starts on a slippery surface, ESP® prevents excessive wheel slippage by controlling engine power and braking.



SUPER SAFETY AT HIGH SPEEDS

At highway speeds, ESP® gives better control during sudden braking, preventing instability.





TECHNICAL SPECIFICATIONS

MODEL VARIANTS		PETROL	PETROL CHASSIS## (Incompletely built vehicle)	CNG	CNG CHASSIS## (Incompletely built vehicle)	
	Engine	Advanced K-Series Dual Jet, Dual VVT	Advanced K-Series Dual Jet, Dual VVT	Advanced K-Series Dual Jet, Dual VVT	Advanced K-Series Dual Jet, Dual VVT	
	Maximum Power	59.4 kW (80.7PS) @6000 rpm	59.4 kW (80.7PS) @6000 rpm	52.7 kW (71.6PS) @6000 rpm	52.7 kW (71.6PS) @6000 rpm	
Specifications	Maximum Torque	104.4 Nm@2900 rpm	104.4 Nm@2900 rpm	95 Nm@2800 rpm	95 Nm@2800 rpm	
	Engine Capacity	1197 cc	1197 cc	1197 cc	1197 cc	
	Fuel Distribution	MPFI	MPFI	MPFI	MPFI	
Transmission	Туре	5MT	5MT	5MT	5MT	
	Gearbox	5 Forward and 1 Reverse	5 Forward and 1 Reverse	5 Forward and 1 Reverse	5 Forward and 1 Reverse	
	Clutch	Single Plate Dry Friction	Single Plate Dry Friction	Single Plate Dry Friction	Single Plate Dry Friction	
Brake	Front	Ventilated Disc Brake	Ventilated Disc Brake	Ventilated Disc Brake	Ventilated Disc Brake	
	Rear	Drum Brake	Drum Brake	Drum Brake	Drum Brake	
Suspension & Steering	Front	MacPherson Strut with Coil Spring	MacPherson Strut with Coil Spring	MacPherson Strut with Coil Spring	MacPherson Strut with Coil Spring	
	Rear	Leaf Spring Rigid Axle	Leaf Spring Rigid Axle	Leaf Spring Rigid Axle	Leaf Spring Rigid Axle	
	Steering	Manual- Rack and Pinion	Manual- Rack and Pinion	Manual- Rack and Pinion	Manual- Rack and Pinion	
Vheel and Tyre	Tyre	155R13 LT 8PR	155R13 LT 8PR	155R13 LT 8PR	155R13 LT 8PR	
Measurement	Length	3800 mm	3800 mm	3800 mm	3800 mm	
	Width	1562 mm	1562 mm	1562 mm	1562 mm	
	Height	1883 mm	1883 mm	1883 mm	1883 mm	
	Wheel Base	2110 mm	2110 mm	2110 mm	2110 mm	
	Front Track	1345 mm	1345 mm	1345 mm	1345 mm	
	Rear Track	1330 mm	1330 mm	1330 mm	1330 mm	
	Length of Deck	2183 mm	NA	2183 mm	NA NA	
	Width of Deck	1488 mm	NA	1488 mm	NA	
	Height of Deck	300 mm	NA	300 mm	NA	
	Turning Radius	4.3 m	4.3 m	4.3 m	4.3 m	
Performance	Top Speed	80 km/h	80 km/h	80 km/h	80 km/h	
	Gradeability	34%	34%	34%	34%	
Weight	GVW	1620 kg	1620 kg	1620 kg	1620 kg	
	Kerb	870 kg	775 kg	990 kg	895 kg	
	Payload	750 kg	NA	630 kg	NA	
	Seating Capacity	Driver + 1	Driver + 1	Driver + 1	Driver + 1	
Capacity	Fue l Tank	30L	30L	CNG Cylinder (Water Equivalent) =70L (35Lx2) Gasoline = 5L (For Emergency Use)	CNG Cylinder (Water Equivalent) =7 (35Lx2) Gasoline = 5L (For Emergency Use)	

EQUIPMENT LIST	VARIANT	PETRO	PETROL CHASSIS*** (Incompletely built vehicle)	CNG	CNG CHASSIS*** (Incompletely built vehicle)
Exterior	Tailgate Opening Function with Handle	S		S	
	Tailgate Chain	S		S	
	Front Wiper (2-Speed) with Windshield Washer	S	S	S	S
	ORVM (Driver and Co-Driver)	S	S	S	S
	Spare Tyre	S	S	S	S
	Rope Hooks	S		S	
	Mud Flap (Front)	S	S	S	S
	Rear Fender	S		S	
	Front Body Graphics			S	S
	Side Body Graphics			S	S
	Cabin Main Light (2-Position)	S	S	S	S
	Driver Side Sun Visor	S	S	S	S
	Driver Side Pocket	S	S	S	S
	Sliding Back Window	S	S	S	S
Interior (Comfort, Convenience & Utility)	Assist Grip (Driver & Co-Driver)	S	S	S	S
	Bottle Holder	S	S	S	S
(Connort, Convenience & Othicy)	Instrument Panel Upper Tray (2 Numbers)	S	S	S	S
	12V Accessory Socket	S	S	S	S
	Floor Carpet	S	S	S	S
	3-Spoke Steering Wheel	S	S	S	S
	Sliding Driver Seat	S	S	S	S
	Seat Belts (Retractable)	S	S	S	S
^Safety Features	Locking Glove Box (With Key)	S	S	S	S
	Headlamp Levelling	S	S	S	S
	Steering Lock	S	S	S	S
	Reflective Tape (Front)	S	S	S	S
	Reflective Tape (Rear)	S		S	
	Reflector Front (White)	S	S	S	S
	Reflector Rear (Red)	S		S	
	First-Aid Kit	S	S	S	S
	Warning Triangle	S	S	S	S
	Hazard Lamp	S	S	S	S
	Front Disk Brake	S	S	S	S
	Electronic Stability Program (ESP®)	S	S	S	S
	ABS+EBD	S	S	S	S
	Stepney Lock Provision	S	S	S	S
	Battery Lock Provision	S	S	S	S
	Fire Extinguisher			S	S
	Rear Parking Sensor System	S	S	S	S
	Seat Belt Reminder (Driver & Co-Driver)	S	S	S	S
	Engine Immobilizer	S	S	S	S

Body Colour Options

Dealer Stamping Area



Metallic Silky Silver









For more details contact | Toll free No: 1800 102 1800

Visit us at: https://www.marutisuzukicommercial.com/super-carry

Maruti Suzuki India Limited, reserves the right to change without notice, prices, colours, equipments, specifications, variants and also to discontinue models. Accessories and features shown in the pictures may not be part of standard equipment, and will differ according to the variant. For variant-specific features, refer to the equipment list. Colours shown may vary from actual body colours due to printing on paper. Images used are for illustration purposes only. *3 years or 100 000 km whichever is earlier. Terms and conditions apply. Creative Visualization. Black Glass on the vehicle is due to lighting effect. Features and accessories shown may not be part of standard fitment. *Based on JATO Dynamics' study dated January 15, 2025, conducted for all fuel type segment vehicles with GVW less than or equal to 2 Tonnes. ESP is the registered trademark of Mercedes-Benz Group AG.

##For Cab Chassis variants, application body to be fabricated as per instructions in Owner's Manual. 'For details on functioning of safety features, kindly refer to the Owner's Manual.